

GENERAL NOTES FOR GRADING

- ALL WORK SHALL CONFORM WITH THE "GREENBOOK" STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (SSPWC), 2012 EDITION AND THE LATEST REVISIONS THERETO, THE WORK AREA TRAFFIC CONTROL HANDBOOK (W.A.T.C.H. MANUAL), A.D.A, TITLE 24 REQUIREMENTS, AND THE 2013 C.B.C. UNLESS SPECIFIED OTHERWISE IN THE CONTRACT SPECIFICATIONS.
- THROUGHOUT ALL PHASES OF CONSTRUCTION, INCLUDING SUSPENSION OF WORK, UNTIL FINAL ACCEPTANCE OF THE PROJECT, THE CONTRACTOR SHALL KEEP THE WORK SITE CLEAN AND FREE FROM RUBBISH AND DEBRIS. THE CONTRACTOR SHALL ALSO ABATE DUST NUISANCE BY CLEANING, SWEEPING AND SPRINKLING WITH WATER AND USING DUST FENCES OR OTHER METHODS AS DIRECTED BY THE CONSTRUCTION MANAGER OR FIELD INSPECTOR THROUGHOUT THE CONSTRUCTION OPERATION.
- KEEP A RECORD OF CHANGES THAT OCCUR DURING CONSTRUCTION AND SUBMIT THIS RECORD TO THE OWNER CERTIFIED AS "RECORD DRAWING" PLANS.
- ALL DAMAGE CAUSED TO PUBLIC STREETS, INCLUDING HAUL ROUTES, ALLEYS, SIDEWALKS, CURBS OR STREET FURNISHINGS, OR TO PRIVATE PROPERTY SHALL BE REPAIRED AT THE SOLE EXPENSE OF THE CONTRACTOR TO THE ENGINEER'S SATISFACTION.
- THE CONTRACTOR SHALL REMOVE AND REPLACE ANY EXISTING BROKEN OR DAMAGED SIDEWALK, CURB, GUTTER OR ASPHALT PAVING (PATCH, REPAIR OR OVERLAY) CAUSED BY THEIR WORK ON THIS PROJECT AT THE DIRECTION OF THE SCHOOL DISTRICT AT NO ADDITIONAL COST TO THE OWNER.
- ALL UNDERGROUND SEWER, STORM DRAIN, AND WATER PIPELINES, ELECTRIC POWER, TELEPHONE OR CABLE TV CONDUITS AND CABLE AND GAS PIPELINES SHALL BE INSTALLED PRIOR TO CONSTRUCTION OF CURBS, GUTTERS, SIDEWALKS AND PAVEMENT.
- UPON MOBILIZATION THE CONTRACTOR SHALL POthOLE AND EXPOSE THE EXISTING UTILITIES AT ALL CROSSINGS AND AT THE POINT OF TIE-IN, THEN CONTACT THE ENGINEER TO VERIFY THE ELEVATION OF THE EXISTING FACILITIES.
- SURVEY MONUMENTS SHALL BE PRESERVED AND REFERENCED BEFORE CONSTRUCTION AND RE-PLACED AFTER CONSTRUCTION PURSUANT TO SECTION 2-9 OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (SSPWC).
- EITHER WATER OR DUST PALLIATIVE, OR BOTH, MUST BE APPLIED FOR THE ALLEVATION OR PREVENTION OF EXCESSIVE DUST RESULTING FROM THE LOADING OR TRANSPORTATION OF EARTH FROM OR TO THE PROJECT SITE OR PRIVATE AND PUBLIC ROADWAYS.
- CONSTRUCT STRAIGHT GRADES BETWEEN ELEVATIONS SHOWN ON PLAN UNLESS INTERRUPTED BY A GRADE CHANGE LINE. ANY DEVIATION FROM THE GRADING PLAN MUST HAVE PRIOR APPROVAL FROM THE ENGINEER.
- ALL AREAS TO RECEIVE COMPACTED FILL SHALL BE INSPECTED AND APPROVED BY THE SOILS ENGINEER (AND ENGINEERING GEOLOGIST, WHERE EMPLOYED) AFTER REMOVAL OF UNSUITABLE MATERIAL AND EXCAVATION OF KEYWAYS AND BENCHES, AND PRIOR TO PLACEMENT OF SUBSURFACE DRAINAGE SYSTEMS OR ANY FILLS.
- ALL SOILS OR ROCK MATERIALS DEEMED UNSUITABLE FOR PLACEMENT IN COMPACTED FILL BY THE SOILS ENGINEER SHALL BE REMOVED FROM THE SITE.
- ALL TREE ROOTS, ABANDONED IRRIGATION LINES, UTILITY SERVICES, SEPTIC TANKS AND SIMILAR MATERIALS SHALL BE REMOVED FROM THE SITE AND VOIDS CREATED THEREBY SHALL BE PROPERLY FILLED AND COMPACTED AS DIRECTED BY THE GEOTECHNICAL ENGINEER WITHIN THE LIMITS OF WORK UNDER THE FIELD.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING STORM DAMAGE PREVENTION MEASURES OR EROSION CONTROL DEVICES AND/OR TO PERFORM CERTAIN GRADING TO PREVENT SOIL OR EXCESS RUNOFF FROM FLOWING INTO PUBLIC STREETS OR ADJACENT PROPERTIES. IN THE EVENT OF SUCH AN OCCURRENCE, CLEANUP SHALL COMMENCE IMMEDIATELY. SHOULD CITY FORCES OR THE CITY CONTRACTOR PERFORM ANY CLEANUP RESULTING FROM THIS DEVELOPMENT, THE CONTRACTOR SHALL PAY THE COST INCURRED WITHIN TEN (10) WORKING DAYS UPON RECEIPT OF BILLING.
- THE CONTRACTOR OR HIS AGENT SHALL BE RESPONSIBLE FOR REMOVAL AND CLEANUP OF ANY SPILL ON PUBLIC STREETS DURING THE GRADING OPERATION, AS WELL AS REPAIR OF DAMAGE TO HAUL ROUTES AND EXISTING FACILITIES.
- ALL EQUIPMENT USED TO HAUL EXCAVATION OR FILL MATERIAL FROM OR TO THE SITE SHALL FOLLOW A DESIGNATED ROUTE, OR ROUTES IN GOING TO AND FROM THE SITE. THE CONTRACTOR SHALL BE ENTITLED TO THE DESIGNATION OF A ROUTE PROVIDING ACCESS TO A SPECIFIED PLACE OTHER THAN THE SITE, AFTER SHOWING TO THE SATISFACTION OF THE CITY BUILDING OFFICIAL THAT SUCH SPECIFIED PLACE IS A PLACE WHERE EXCAVATION MATERIAL MAY BE REASONABLY DEPOSITED OR FILL MATERIAL MAY BE OBTAINED. A SEPARATE ENCROACHMENT PERMIT IS REQUIRED WHEN IT IS NECESSARY TO FLAG TRAFFIC OR INSTALL ANY TRAFFIC CONTROL DEVICES NO CITY RIGHT-OF-WAY.
- ANY EARTH ROCK, GRAVEL, SAND, STONE OR OTHER EXCAVATED MATERIAL DEPOSITED OR CAUSED TO ROLL, FLOW OR WASH UPON ANY PUBLIC PLACE OR PRIVATE PROPERTY SHALL BE REMOVED FROM SUCH PUBLIC PLACE OR PRIVATE PROPERTY BY THE END OF THE WORKDAY BY THE CONTRACTOR RESPONSIBLE FOR THE DEPOSITION, IF AN ADVERSE CONDITION IS CAUSED BY DEPOSIT, THE CONDITION SHALL BE CORRECTED IMMEDIATELY.
- EVERY EFFORT SHOULD BE MADE TO ELIMINATE THE DISCHARGE OF NON-STORMWATER FROM THE PROJECT SITE AT ALL TIMES.
- ALL TRUCKS HAULING DIRT, SAND, OIL, OR OTHER LOOSE MATERIALS ON A HIGHWAY ARE TO BE COVERED OR SHOULD MAINTAIN AT LEAST TWO FEET OF FREEBOARD IN ACCORDANCE WITH THE REQUIREMENTS OF CALIFORNIA VEHICLE CODE SECTION 23114. (FREEBOARD MEANS VERTICAL SPACE BETWEEN THE TOP OF THE LOAD AND TOP OF THE TRAILER).
- NO PERSON SHALL, WHEN HAULING ANY EARTH, SAND, GRAVEL, ROCK, STONE OR OTHER EXCAVATED MATERIAL OR DEBRIS OVER ANY PUBLIC STREET, ALLEY OR OTHER PUBLIC PLACE, ALLOW SUCH MATERIAL TO BLOW OR SPILL OVER UPON SUCH STREET, ALLEY OR PUBLIC PLACE OR ADJACENT PRIVATE PROPERTY OR ANY WATER BODIES, CREEKS OR STREAMS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CLEANUP AND REMOVAL OF ANY CONSTRUCTION OR SOILS MATERIALS DEPOSITED ON THE PUBLIC RIGHT-OF-WAY, PUBLIC WATERS OR ADJACENT PRIVATE PROPERTY.
- CONSTRUCT STRAIGHT GRADES BETWEEN ELEVATIONS SHOWN ON PLANS UNLESS INTERRUPTED BY A GRADE CHANGE LINE. ANY DEVIATION FROM THE GRADING PLAN MUST HAVE PRIOR APPROVAL FROM THE ENGINEER.

EARTHWORK NOTICE TO CONTRACTOR: NO EARTHWORK ANALYSIS HAS BEEN COMPLETED WITH RESPECT TO VOLUMES OF SOILS TO BE EXCAVATED, PLACED, OR IMPORTED IN ORDER TO PROVIDE THE FINISHED GRADES SHOWN ON THE PLANS. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR VERIFYING THE EARTHWORK QUANTITIES NECESSARY TO COMPLETE THE PROJECT.


IRRIGATION NOTICE TO CONTRACTOR:
A WORKING IRRIGATION SYSTEM EXISTS ON THIS SITE. CONTRACTOR SHALL TAKE EXTREME CARE AS TO NOT DAMAGE EXISTING IRRIGATION SYSTEM. CONTRACTOR SHALL REPAIR IRRIGATION CONTROL WIRES OR OTHER LOW VOLTAGE WIRES IN AREAS THAT ARE DAMAGED BY CONTRACTOR. CONTRACTOR SHALL REPAIR AND/OR REPLACE BROKEN LINES AND/OR EQUIPMENT DAMAGED DURING HIS COURSE OF CONSTRUCTION. REPAIR MATERIALS SHALL BE AS THE SAME AS EXISTING MATERIAL OR AS REQUIRED BY THE OWNER AT NOT ADDITIONAL COST TO THE OWNER.

GENERAL NOTES TO CONTRACTOR

- THE CONTRACTOR'S ATTENTION IS DIRECTED TO SECTION 7-10, PUBLIC CONVENIENCE AND SAFETY, OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (GREENBOOK), IN REGARDS TO SAFETY ORDERS.
- SCOPE OF WORK:
A. FURNISH ALL LABOR, SUPERVISION, MATERIALS, EQUIPMENT & FACILITIES NECESSARY TO FURNISH, FABRICATE, DELIVER, STORE AND INSTALL ALL WORK NOTED ON THE DRAWINGS.
B. THE CONTRACTOR SHALL FURNISH & INSTALL ALL WORK NECESSARY TO MAKE A COMPLETE SYSTEM WHETHER OR NOT SUCH DETAILS ARE MENTIONED IN THESE SPECIFICATIONS OR SHOWN ON THE PLANS, BUT WHICH ARE OBVIOUSLY NECESSARY TO MAKE A COMPLETE SYSTEM, EXCEPTING ONLY THOSE PORTIONS THAT ARE SPECIFICALLY MENTIONED HEREIN OR PLAINLY MARKED ON THE ACCOMPANYING DRAWINGS AS BEING INSTALLED UNDER ANOTHER SECTION OF THE SPECIFICATION.
- SITE INSPECTION: CONTRACTOR SHALL VISIT THE SITE OF WORK PRIOR TO SUBMISSION OF HIS BID AND THOROUGHLY FAMILIARIZE HIMSELF WITH THE WORKING CONDITIONS & EXACT NATURE OF THE WORK. SUBMISSION OF A BID ACKNOWLEDGES FULL RESPONSIBILITY FOR FURNISHING A COMPLETE & FUNCTIONAL SYSTEM, NO CHANGES IN CONTRACT WILL MADE TO ACCOMMODATE OR ALLOW EXTRA FUNDING FOR ANY OMISSIONS WHICH RESULTS FROM A FAILURE TO THOROUGHLY MAKE THE EXAMINATION.
- IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO VERIFY AVAILABLE SPACES FOR INSTALLING THE WORK.
- COORDINATION: THE DRAWINGS ARE DIAGRAMMATIC & INTENDED TO SHOW SCOPE. CONTRACTOR SHALL COORDINATE HIS WORK WITH OTHER TRADES TO PROVIDE BEST ARRANGEMENT OF ALL DUCT, PIPES, CONDUIT, ETC.
- WORKMANSHIP: THE WORK SHALL BE ACCOMPLISHED BY THE USE OF COMPETENT MECHANICS SKILLED IN THEIR TRADE. THE ENGINEER AND ARCHITECT SHALL HAVE THE RIGHT TO INTERPRET COMPLIANCE OF WORKMANSHIP WITH THE CONTRACT DOCUMENTS.
- MATERIALS: ALL MATERIALS, APPLIANCES & EQUIPMENT SHALL BE NEW & THE BEST OF THEIR RESPECTIVE KIND, FREE FROM ALL DEFECTS AND OF THE MAKE, BRAND, AND QUANTITY SPECIFIED.
- CLEAN-UP: UPON COMPLETION OF THE WORK UNDER THIS SECTION THE CONTRACTOR SHALL REMOVE ALL SURPLUS MATERIALS, EQUIPMENT & DEBRIS INCIDENTAL TO THIS WORK & LEAVE THE PREMISES CLEAN AND ORDERLY.

SHEET INDEX	
SHEET	DESIGNATION
C001	TITLE SHEET
C002	PRECISE GRADING AND DRAINAGE PLAN
C003	PRECISE GRADING AND DRAINAGE DETAILS
C004	WATER POLLUTION CONTROL PLAN
C005	WATER POLLUTION CONTROL DETAILS
C006	FIELD COOLING SYSTEM PLAN
C007	FIELD COOLING SYSTEM DETAILS
C008	FIELD COOLING SYSTEM DETAILS

SITE IMPROVEMENT PLANS FOR COMPTON COMMUNITY COLLEGE DISTRICT COMPTON FOOTBALL FIELD



ABBREVIATIONS			
ABND	ABANDONED	MH	MANHOLE
AC	ASPHALT PAVEMENT	NG	NATURAL GROUND
AP	ANGLE POINT	N.I.C.	NOT IN CONTRACT
BLDG	BUILDING	P.C.C.	PORTLAND CEMENT CONCRETE
BC	BEGINNING OF CURVE	PL	PROPERTY LINE
BW	BACK OF WALK	PIV	POST INDICATOR VALVE
CL	CENTERLINE	PP	POWER POLE
CF	CURB FACE HEIGHT	RCE	REGISTERED CIVIL ENGINEER
CLF	CHAIN LINK FENCE	RR	RAILROAD
CONC	CONCRETE	S	SLOPE
DCV	DETECTOR CHECK VALVE	SDMH	STORM DRAIN MANHOLE
DESC	DESCRIBED	SL	STREET LIGHT
D/W	DRIVEWAY	SMH	SEWER MANHOLE
DI	DROP INLET	S.P.P.W.C.	STANDARD PLANS FOR PUBLIC WORKS CONSTRUCTION (LATEST EDITION).
EP	EDGE OF PAVEMENT	S.P.P.W.C.	STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (GREEN BOOK), LATEST EDITION
EC	END OF CURVE	SW	SIDEWALK
EX	EXISTING	T.B.M.	TEMPORARY BENCHMARK
FDC	FIRE DEPARTMENT CONNECTION	TC	TOP OF CURB
FH	FIRE HYDRANT	TELE	TELEPHONE
FL	FLOWLINE	TG	TOP OF GRATE
FS	FINISH SURFACE	TCO	TOP OF CLEANOUT
GA	GUY ANCHOR	TS	TRAFFIC SIGN
GB	GRADE BREAK	TW	TOP OF WALL
GP	GUARD POST	TYP.	TYPICAL
GV	GAS VALVE	UDG	UNDERGROUND CONDUIT
HB	HOSE BIBB	UTIL	UTILITY
HP	HIGH POINT	WM	WATER METER
ICV	IRRIGATION CONTROL VALVE	WV	WATER VALVE
INV	INVERT	W VLT	WATER VAULT
IP	IRON PIPE	WF	VERIFY IN FIELD
L	LENGTH	VLT	VAULT
LIP	LIP OF GUTTER		
LP	LIGHT POLE		
L T & T	LEAD TACK AND TAG		

HORIZONTAL CONTROL

A CAD GEOMETRIC ELECTRONIC FILE SHALL BE MADE AVAILABLE TO THE CONTRACTOR UPON REQUEST FOR THE CONTRACTOR'S SURVEYOR TO LAYOUT THE CONSTRUCTION STAKING OF THE PROJECT. THE SURVEYOR OR CONTRACTOR WILL NEED TO SIGN A WAIVER FORM BEFORE RELEASE OF ANY CAD ELECTRONIC DRAWINGS.



TEMPORARY BENCH MARK: ELEVATION: 58.29 FT.

TEMPORARY BENCHMARK (T.B.M.) BEING A PUNCH MARK ON THE STORM DRAIN MANHOLE RIM AT THE NORTH EAST CORNER OF THE TRACK AS NOTED ON THE GRADING PLAN.

EXISTING UNDERGROUND STRUCTURES & UTILITIES

THE LOCATIONS OF THE EXISTING UNDERGROUND UTILITIES, AS SHOWN ON THIS PLAN, WERE OBTAINED FROM SOURCES OF VARYING RELIABILITY. NO REPRESENTATION IS MADE AS TO THE ACCURACY OR COMPLETENESS OF SAID UTILITY INFORMATION. THE CONTRACTOR IS CAUTIONED THAT ONLY ACTUAL EXCAVATION WILL REVEAL THE LOCATIONS OF SUCH UNDERGROUND UTILITIES. CONTRACTOR ASSUMES RESPONSIBILITY FOR THE UNDERGROUND UTILITY PIPES, CONDUITS, OR STRUCTURES SHOWN OR NOT SHOWN ON THESE PLANS. VERIFY LOCATIONS OF EXISTING UTILITIES PRIOR TO EXCAVATION OR IMPROVEMENT. TAKE PRECAUTIONARY MEASURES TO PROTECT THE UTILITY LINES.

GHATRODE RAMMON ARCHITECTS
Architecture • Planning • Interior Design
11435 93RD
COSTA MESA, CA 92627
Tel: 714.835.8200
Fax: 714.835.8202



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES
FILE NO.:
APPL. NO.:
AC _____ FL _____ SS _____
DATE _____

**COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221**

REVISIONS:

▲	
▲	
▲	
▲	
▲	
▲	
▲	
▲	
▲	
▲	
▲	
▲	
▲	


Date: 06/10/15
Job: 1529
Scale: NONE
Drawn: AU

C001
SHEET -- OF
REF:

PLAN PREPARED BY:
FPL FPL and Associates, Inc.
Traffic • Transportation • Civil
10 Corporate Park, Suite 310
Irvine, CA 92606
PHONE: 949-252-1888

TITLE SHEET




Copyright © 2015 Ghatrode Rammon Architects, LLP



GRADING NOTE:
 THE CONTRACTOR SHALL UTILIZE LASER-CONTROLLED EQUIPMENT FOR THE GRADING OF THE FIELD TO ENSURE ACCURACY IN GRADING TOLERANCES. FINAL GRADE SHALL BE ESTABLISHED TO WITHIN A TOLERANCE OF (.04') OF THE DESIGNED FINISH CONTOURS / GRADES.

- CONSTRUCTION NOTES:**
- PROTECT EXISTING IMPROVEMENTS IN PLACE.
 - CONSTRUCT ASPHALT CONCRETE PAVEMENT 'SYNTHETIC TURF USAGE' PER TABLE 1 ON SHEET C003.
 - CONSTRUCT 18" x 18" CATCH BASIN PER DETAIL 3 ON SHEET C003.
 - CONSTRUCT 4" SDR-35 PVC DRAINAGE PIPE. SEE CORRESPONDING TRENCH DETAIL ON SHEET C003.
 - CONSTRUCT 6" SDR-35 PVC DRAINAGE PIPE. SEE CORRESPONDING TRENCH DETAIL ON SHEET C003.
 - CONSTRUCT 8" SDR-35 PVC DRAINAGE PIPE. SEE CORRESPONDING TRENCH DETAIL ON SHEET C003.
 - CONNECT NEW STORM DRAIN PIPE INTO EXISTING STORM DRAIN PIPE.
 - CONNECT NEW CATCH BASIN INTO EXISTING STORM DRAIN PIPE.
 - CONSTRUCT ACO SPORT SYSTEM 4000 CHANNEL CATCH BASIN PER DETAIL 10 ON A002.
 - CONSTRUCT ACO SPORT SYSTEM 4000 IN-LINE CATCH BASIN.
 - CONSTRUCT SYNTHETIC TURF OVER DRAINAGE MAT PER ARCHITECTURAL PLANS.
 - FIELD COOLING SYSTEM VAULT PER 'E' ON SHEET C008.
 - REMOVE AND DISPOSE EXISTING DRAIN INLET. PLUG EXISTING STORM DRAIN ENDS.
 - REMOVE INTERFERE PORTION OF EXISTING 6" STORM-DRAIN LINE FOR INSTALLATION OF FIELD COOLING SYSTEM VAULT. PLUG EXISTING ENDS OF STORM DRAIN PIPE.
 - ABANDON IN PLACE EXISTING 6" STORM-DRAIN LINE.
 - REMOVE EXISTING GOAL POST & FOUNDATION AND INSTALL NEW GOAL POST AND FOUNDATION PER DETAILS ON A002.
 - SEE DETAIL 14 ON A002 FOR JOIN CONDITION.
 - REMOVE AND DISPOSE EXISTING ELECTRICAL VAULTS.
 - CONSTRUCT ELECTRICAL COMMUNICATION BOX.



- LEGEND:**
- [Symbol] = NEW SYNTHETIC TURF OVER DRAINAGE MAT OVER 3" AC OVER 4" BASE
 - [Symbol] = PROPOSED CONTOUR LINE
 - [Symbol] = EXISTING CONTOUR LINE
 - [Symbol] = FIELD COOLING VAULT



NOTE: CONTRACTOR IS REQUIRED TO RESTORE ALL EXISTING IMPROVEMENTS TO THE SAME CONDITION, THAT ARE NOT PART OF THIS PROJECT, THAT EXISTED PRIOR TO HIS STARTING CONSTRUCTION.

GARTRUDE BARRON ARCHITECTS
 Architecture • Planning • Interior Design
 1011 W. 10th STREET, UNIT 8
 COSTA MESA, CA 92626
 PH: 714.668.0900
 FAX: 714.668.0901

Copyright © 2015 Gartrude Barron Architects, LLP



IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 OFFICE OF REGULATION SERVICES

FILE NO.:
 APP. NO.:
 AC: FLS SS
 DATE:

COMPTON COMMUNITY COLLEGE DISTRICT
 COMPTON FOOTBALL FIELD
 1111 E. ARTESIA BLVD., COMPTON, CA 90221
 PRECISE GRADING AND DRAINAGE PLAN

REVISIONS:

Date: 06/10/15
 Job: 1529
 Scale: 1" = 20'
 Drawn: AU

PLAN PREPARED BY:
FPL FPL and Associates, Inc.
 Traffic • Transportation • Civil
 10 Corporate Park, Suite 310
 Irvine, CA 92606
 PHONE: 949-252-1688

TRENCHING DETAILS FOR STORM DRAIN PIPE & WATER PIPE 4-INCHES AND OVER

EXCAVATION PROTECTION NOTE: TRENCHES MORE THAN 5 FEET DEEP MUST BE SHORED OR APPROPRIATELY SLOPED PER OSHA STANDARDS FOR THE CONSTRUCTION INDUSTRY, STANDARD #1926.652 'REQUIREMENTS FOR PROTECTIVE SYSTEMS'.

TRENCH EXCAVATION, BEDDING, & BACKFILL NOTES:

EXCAVATION NOTE: EXCAVATION 5.0 FEET AND DEEPER SHALL BE SUPPORTED AS SET FORTH IN THE RULES, ORDERS AND REGULATIONS OF THE CALIFORNIA DEPARTMENT OF INDUSTRIAL RELATIONS, DIVISION OF INDUSTRIAL ACCIDENTS. THE CONTRACTOR SHALL SUBMIT A DETAIL SHOWING THE DESIGN OR SHORING, BRACING SLOPING OR OTHER PROVISIONS TO BE MADE FOR WORKER PROTECTION FROM THE HAZARDS OF CAVING GROUND DURING THE EXCAVATION. THE PLAN SUBMITTED SHALL BE SIGNED BY A REGISTERED CIVIL OR STRUCTURAL ENGINEER CERTIFIED THAT THE PLAN COMPLIES WITH ALL OSHA CONSTRUCTION SAFETY ORDERS.

BEDDING SHALL CONSIST OF COARSE SAND WITH SAND EQUIVALENT OF 35 OR GREATER. NO ANGULAR STONES OR PEA GRAVELS WILL BE ALLOWED IN PIPE BEDDING.



BEDDING & BACKFILL SHALL BE PLACED IN ACCORDANCE WITH SECTION 306-1.2.1 AND 306-1.3 OF THE "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (S.S.P.W.C.), 2009 EDITION" AND AS SUPPLEMENTED HEREIN. TRENCH BACKFILL SLURRY PER SECTION 201-1. EXISTING SITE SOILS, WHERE CONDITIONS DICTATE HEREIN, ARE CONSIDERED SUITABLE FOR BACKFILLING OF UTILITY TRENCHES PROVIDED THEY ARE FREE OF DEBRIS, PARTICLES GREATER THAN 4 INCHES IN MAXIMUM DIMENSION, ORGANIC MATTER OR OTHER DELETERIOUS MATERIALS. EXTREME CARE SHALL BE TAKEN TO AVOID DAMAGE TO CONDUITS, PIPES, AND ANY APPURTENANCES. PER SECTION 306-1.2.1 OF S.S.P.W.C., IF SOFT, SPONGY, UNSTABLE OR OTHER UNSUITABLE MATERIAL IS ENCOUNTERED UPON WHICH THE BEDDING MATERIAL OR PIPE IS TO BE PLACED, THIS MATERIAL SHALL BE REMOVED TO A DEPTH ORDERED BY THE CIVIL ENGINEER AND REPLACED WITH BEDDING MATERIAL SUITABLY DENSIFIED.

COMPACTION METHODS: ALL BEDDING & BACKFILL COMPACTION SHALL BE BY HAND-OPERATED, PLATE-TYPE, VIBRATORY, OR OTHER SUITABLE HAND-TAMPERS IN AREAS NOT ACCESSIBLE TO LARGER ROLLERS OR COMPACTORS. EXTREME CARE SHALL BE TAKEN TO AVOID DAMAGE TO CONDUITS, PIPES, AND ANY APPURTENANCES. WATER DENSIFICATION BY INUNDATION OR JETTING SHALL NOT BE PERMITTED WITHOUT PRIOR WRITTEN APPROVAL FROM CIVIL ENGINEER.




SHIELDING: WHEN EXCAVATION DEPTHS OR SOIL CONDITIONS REQUIRE SHORING OR USE OF A TRENCH BOX, THE BOTTOM OF THE SHORING OR TRENCH BOX SHOULD BE PLACED NO LOWER THAN THE TOP OF THE PIPE. THIS PREVENTS DISRUPTION OF THE BACKFILL ENVELOPE WHEN REMOVING THE SHORING OR TRENCH BOX. IF THIS PRACTICE CANNOT BE FOLLOWED, CONSIDERATION SHOULD BE GIVEN TO LEAVING THE SHORING IN PLACE.

WARNING TAPE NOTES (STORM DRAIN):
A METALLIC LINED TAPED FOR UNDERGROUND PIPES, MARKED "CAUTION BURIED STORM DRAIN LINE BELOW", IN POLYETHYLENE FILM COLOR GREEN, INSTALLED ABOVE PIPE, 6" WIDE.

WARNING TAPE NOTES (WATER PIPE):
A METALLIC LINED TAPED FOR UNDERGROUND PIPES, MARKED "CAUTION BURIED WATER LINE BELOW", IN POLYETHYLENE FILM COLOR BLUE, INSTALLED ABOVE PIPE, 6" WIDE.



USAGE TYPE	TABLE 1 ASPHALT CONCRETE PAVEMENT STRUCTURAL SECTION
SYNTHETIC TURF	3" THICK A.C. OVER 4" THICK C.A.B. OVER 12" THICK SCARIFICATION PER DETAIL BELOW.



1818 CAST IRON GRATE
PARKWAY ONLY 58 lbs.
PARKWAY TRAFFIC 27 lbs. 49 lbs.

1818 STEEL GRATES
PARKWAY ONLY 44 lbs. 65 lbs.

1818 STEEL COVER
PARKWAY TRAFFIC 44 lbs. 65 lbs.

1818 TOP SECTION (WITH GALVANIZED FRAME)
NOTE: USE 12" 18" 24" LOWERS TO INCREASE DEPTH UP TO A MAXIMUM OF 72"

1818 LOWER SECTION (NO FRAME)
NOTE: USE 12" 18" 24" LOWERS TO INCREASE DEPTH UP TO A MAXIMUM OF 72"

1818 BASE
WT. 270 lbs

18" x 18" CATCH BASIN
1818 CB

NOTES:
1. GRATES AND COVERS AVAILABLE PAINTED BLACK OR GALVANIZED
2. "ADA" GRATES AVAILABLE IN PARKWAY & TRAFFIC
3. "HEEL PROOF" GRATES AVAILABLE IN PARKWAY & TRAFFIC
4. A TOP SECTION WITH FRAME MUST BE USED IF BOLT DOWN REQUIRED

TOP SECTION	HT.	LBS.	KNOCK-OUT
1818 TG	6"	215	NONE
1818 T12	12"	370	(4) 5" x 10"
1818 T18	18"	555	(4) 9" x 11"
1818 T24	24"	785	(4) 9" x 11"

EXTENSION SECTION	HT.	LBS.	KNOCK-OUT
1818 EG	6"	215	NONE

LOWER SECTION	HT.	LBS.	KNOCK-OUT
1818 L12	12"	370	(4) 5" x 10"
1818 L18	18"	555	(4) 9" x 11"
1818 L24	24"	785	(4) 9" x 11"

1818 CB

04-20-95 02-28-00

18" x 18" CATCH BASIN
1818 CB

GARIBAY ARCHITECTS
Architecture • Planning • Interior Design
7075 LINDSEY STREET, SUITE 6
COSTA MESA, CA 92627
PH: 714.665.8029

Copyright © 2015 Glendale Ramon Architects, LLP

Architect Seal

Consultant Seal

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES

FILE NO.:
APPL. NO.:
AC: _____ FL: _____ SS: _____
DATE: _____

COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221


PRECISE GRADING AND DRAINAGE DETAILS

REVISIONS:

Date: 06/10/15
Job: 1529
Scale: NONE
Drawn: AU


PLAN PREPARED BY:
FPL FPL and Associates, Inc.
Traffic • Transportation • Civil
10 Corporate Park, Suite 310
Irvine, CA 92606
PHONE: 949-252-1888

C003
SHEET - OF
XREF:





LEGEND:



- = NEW SYNTHETIC TURF
- = TEMPORARY STABILIZED CONSTRUCTION ENTRANCE
DETAIL 'B' ON SHEET C005
- = TEMPORARY MATERIAL STORAGE AREA
DETAIL 'C' ON SHEET C005
- = TEMPORARY CONCRETE WASTE MANAGEMENT (WM) AREA
WM-8 DETAIL ON SHEET C005
- = TEMPORARY FIBER ROLL PER
CASQA BMP SE-5
- = TEMPORARY CHAIN LINK FENCE WITH
FABRIC SCREEN
- = DIRECTION OF SURFACE FLOW
- = PROPOSED CONTOUR LINE
- = EXISTING CONTOUR LINE
- = FIELD COOLING VAULT



SECTION A-A
NOT TO SCALE



PLAN PREPARED BY:
FPL FPL and Associates, Inc.
Traffic - Transportation - Civil
10 Corporate Park, Suite 310
Irvine, CA 92606
PHONE: 949-252-1688



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES

FILE NO.:	
APPL. NO.:	
AC:	FLS SS
DATE:	

COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221
WATER POLLUTION CONTROL PLAN

REVISIONS:

Date: 06/10/15
Job: 1529
Scale: 1" = 20'
Drawn: AU

C004
SHEET - OF
XREF:

STORM WATER POLLUTION CONTROL NOTES:

- 1. APPROPRIATE BMP'S FOR CONSTRUCTION-RELATED MATERIALS, WASTE, SPILLS OR RESIDUES SHALL BE IMPLEMENTED AND RETAINED ON SITE TO MINIMIZE TRANSPORT FROM THE SITE TO STREETS, DRAINAGE FACILITIES, OR ADJOINING PROPERTY BY WIND OR RUNOFF.
2. SEDIMENT FROM AREAS DISTURBED BY CONSTRUCTION SHALL BE RETAINED ON SITE USING STRUCTURAL CONTROLS TO THE MAXIMUM EXTENT PRACTICABLE.
3. STOCKPILES OF SOIL SHALL BE PROPERLY CONTAINED TO MINIMIZE SEDIMENT TRANSPORT FROM THE SITE TO STREETS, DRAINAGE FACILITIES OR ADJACENT PROPERTIES VIA RUNOFF, VEHICLE TRACKING, OR WIND.
4. ALL REMOVABLE EROSION PROTECTIVE DEVICES SHALL BE IN PLACE AT THE END OF EACH WORKING DAY WHEN THE 5-DAY RAIN PROBABILITY FORECAST EXCEEDS 50%.
5. RUNOFF FROM EQUIPMENT AND VEHICLE WASHING SHALL BE CONTAINED AT CONSTRUCTION SITES UNLESS TREATED TO REDUCE OR REMOVE SEDIMENT AND OTHER POLLUTANTS.
6. ALL CONSTRUCTION CONTRACTOR AND SUBCONTRACTOR PERSONNEL ARE TO BE MADE AWARE OF THE REQUIRED BEST MANAGEMENT PRACTICES AND GOOD HOUSEKEEPING MEASURES FOR THE PROJECT SITE AND ANY ASSOCIATED CONSTRUCTION STAGING AREAS.
7. AT THE END OF EACH DAY OF CONSTRUCTION ACTIVITY ALL CONSTRUCTION DEBRIS AND WASTE MATERIALS SHALL BE COLLECTED AND PROPERLY DISPOSED IN TRASH OR RECYCLE BINS.
8. CONSTRUCTION SITES SHALL BE MAINTAINED IN SUCH A CONDITION THAT AN ANTICIPATED STORM DOES NOT CARRY WASTES OR POLLUTANTS OFF THE SITE. DISCHARGES OF MATERIAL OTHER THAN STORMWATER ONLY WHEN NECESSARY FOR PERFORMANCE AND COMPLETION OF CONSTRUCTION PRACTICES AND WHERE THEY DO NOT CAUSE OR CONTRIBUTE TO A VIOLATION OF ANY WATER QUALITY STANDARD; CAUSE OR THREATEN TO CAUSE POLLUTION, CONTAMINATION, OR NUISANCE; OR CONTAIN A HAZARDOUS SUBSTANCE IN A QUANTITY REPORTABLE UNDER FEDERAL REGULATIONS 40 CFR PARTS 117 AND 302.
9. POTENTIAL POLLUTANTS INCLUDE BUT ARE NOT LIMITED TO: SOLID OR LIQUID CHEMICAL SPILLS; WASTES FROM PAINTS, STAINS, SEALANTS, GLUES, LIMES, PESTICIDES, HERBICIDES, WOOD PRESERVATIVES AND SOLVENTS; ASBESTOS FIBERS, PAINT FLAKES OR STUCCO FRAGMENTS; FUELS, OILS, LUBRICANTS, AND HYDRAULIC, RADIATOR OR BATTERY FLUIDS; FERTILIZERS, VEHICLE/EQUIPMENT WASH WATER AND CONCRETE WASH WATER; CONCRETE, DETERGENT OR FLOATABLE WASTES; WASTES FROM ANY ENGINE/EQUIPMENT STEAM CLEANING OR CHEMICAL DEGREASING AND SUPERCHLORINATED POTABLE WATER LINE FLUSHING. DURING CONSTRUCTION, PERMITTEE SHALL DISPOSE OF SUCH MATERIALS IN A WASHOUT BIN OR SPECIFIED AND CONTROLLED TEMPORARY AREA ON-SITE PHYSICALLY SEPARATED FROM POTENTIAL STORMWATER RUNOFF, WITH ULTIMATE DISPOSAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REQUIREMENTS.
10. DEWATERING OF CONTAMINATED GROUNDWATER, OR DISCHARGING CONTAMINATED SOILS VIA SURFACE EROSION IS PROHIBITED. DEWATERING OF NON-CONTAMINATED GROUNDWATER REQUIRES A NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM PERMIT FROM THE RESPECTIVE STATE REGIONAL WATER QUALITY CONTROL BOARD.
11. GRADED AREAS ON THE PERMITTED AREA PERIMETER MUST DRAIN AWAY FROM THE FACE OF SLOPES AT THE CONCLUSION OF EACH WORKING DAY. DRAINAGE IS TO BE DIRECTED TOWARD DESILTING FACILITIES.
12. THE CONTRACTOR SHALL BE RESPONSIBLE AND SHALL TAKE NECESSARY PRECAUTIONS TO PREVENT PUBLIC TRESPASS ONTO AREAS WHERE IMPOUNDED WATER CREATES A HAZARDOUS CONDITION.
13. THE CONTRACTOR SHALL INSPECT THE EROSION CONTROL WORK AND INSURE THAT THE WORK IS IN ACCORDANCE WITH THE APPROVED PLANS.
14. THE GENERAL CONTRACTOR SHALL NOTIFY ALL SUBCONTRACTORS & MATERIAL SUPPLIERS THAT DUMPING OF CHEMICALS INTO THE STORM DRAIN SYSTEM OR THE WATERSHED IS PROHIBITED.
15. EQUIPMENT AND WORKERS FOR EMERGENCY WORK SHALL BE MADE AVAILABLE AT ALL TIMES DURING THE RAINY SEASON. NECESSARY MATERIALS SHALL BE AVAILABLE ON SITE AND STOCKPILED AT CONVENIENT LOCATIONS TO FACILITATE RAPID CONSTRUCTION OF TEMPORARY DEVICES WHEN RAIN IS IMMINENT.
16. THE CONSTRUCTION GENERAL PERMIT REQUIRES ROUTINE WEEKLY INSPECTIONS OF ALL BMPs AND DAILY INSPECTION DURING RAIN EVENTS TO ENSURE THAT ALL BMPs ARE IMPLEMENTED AND MAINTAINED ACCORDING TO THE SWPPP. IN ADDITION BMP INSPECTIONS AND MAINTENANCE SHALL BE PERFORMED 72 HOURS PRIOR TO A FORECASTED STORM EVENT. THE DEFINITION OF A FORECASTED STORM EVENT IS NOTED IN PRIOR NOTE 16.

THE FOLLOWING BMPs AS OUTLINED IN, BUT NOT LIMITED TO, THE STORMWATER BEST MANAGEMENT PRACTICE HANDBOOK, CONSTRUCTION, CALIFORNIA STORMWATER QUALITY ASSOCIATION, LATEST EDITION, MAY APPLY DURING CONSTRUCTION (ADDITIONAL MEASURES MAY BE REQUIRED IF DEEMED APPROPRIATE BY INSPECTOR):


Table with 2 columns: NON-STORMWATER MANAGEMENT & MATERIAL MANAGEMENT BMPs, and EROSION & SEDIMENTAL CONTROL BMPs. Lists various BMP types such as water conservation, dewatering, paving, erosion control, etc.

EROSION AND SEDIMENT CONTROL - SEDIMENTS FROM AREAS DISTURBED BY CONSTRUCTION SHALL BE RETAINED ON SITE USING AN EFFECTIVE COMBINATION OF EROSION AND SEDIMENT CONTROLS TO THE MAXIMUM EXTENT PRACTICABLE, AND STOCKPILES OF SOIL SHALL BE PROPERLY CONTAINED TO MINIMIZE SEDIMENT TRANSPORT FROM THE SITE TO STREETS, DRAINAGE FACILITIES, OR ADJACENT PROPERTIES VIA RUNOFF, VEHICLE TRACKING, OR WIND.

WASTE AND MATERIALS MANAGEMENT CONTROL - APPROPRIATE BMP'S FOR CONSTRUCTION-RELATED MATERIALS, WASTE, SPILLS OR RESIDUES SHALL BE IMPLEMENTED AND RETAINED ON SITE TO MINIMIZE TRANSPORT FROM THE SITE TO STREETS, DRAINAGE FACILITIES, OR ADJOINING PROPERTY BY WIND OR RUNOFF.

Detail A


Catch Basin / Drain Inlet Protection




- Notes: 1. Catch Basin/Inlet protection shall be installed wherever there is a potential of stormwater or non-stormwater being discharged into it. 2. Inlet protection is required along with other pollution prevention measures such as; erosion control, soil stabilization, and measures to prevent tracking onto paved surfaces. 3. Modify inlet protection as needed to avoid creating traffic hazards. 4. Include inlet protection measures at hillside v-ditches and misc. drainage swales. 5. Inlet protection shall be inspected and accumulated sediments removed. Sediment shall be disposed of properly and in a manner that assures that the sediment does not enter the storm drain system. 6. Additional gravel bag sediment traps shall be placed at intervals as indicated on site plan.

Detail A-2

Catch Basin / Drain Inlet Protection




Concrete Waste Management WM-8



- NOTES: 1. ACTUAL LAYOUT DETERMINED IN FIELD. 2. THE CONCRETE WASHOUT SIGN SHALL BE INSTALLED WITHIN 50 FT. OF THE TEMPORARY CONCRETE WASHOUT FACILITY.

Detail B

Stabilized Construction Entrance




- Notes: 1. Sediments and other materials shall not be tracked from the site by vehicle traffic. The construction entrance roadways shall be stabilized so as to prevent sediments from being deposited into the public roads. 2. Stabilized construction entrance shall be: a. Located at any point where traffic will be entering or leaving a construction site to or from a public right of way, street, alley, and sidewalk or parking area. b. A series of steel plates with "rumble strips", and/or min 4" coarse aggregate with length, width & thickness as needed to adequately prevent any tracking onto paved surfaces. 3. Adding a wash rack with a sediment trap large enough to collect all wash water can greatly improve efficiency. 4. All vehicles accessing the construction site shall utilize the stabilized construction entrance sites.

Street Maintenance

- 1. Remove all sediment deposited on paved roadways immediately. 2. Sweep paved areas that receive construction traffic whenever sediment becomes visible. 3. Pavement washing with water is prohibited if it results in a discharge to the storm drain system.

Detail C



Material Storage



- Notes: 1. Dirt and other construction related materials placed in the street or on other impervious surfaces must be contained with sandbags or other measures to prevent transport to the stormdrain system. Any construction material stored or stockpiled on-site shall be protected from being transported by the force of wind or water. Cover material with plastic sheets (min. 10 mil.) with gravel bags for anchoring.

NPDES STORM WATER CONSTRUCTION GENERAL PERMIT 2009-0009-DWQ (AS AMENDED BY 2010-0014-DWQ & 2012-006-DWQ). BEFORE CONSTRUCTION ACTIVITY CAN COMMENCE A STORM WATER POLLUTION PREVENTION PLAN (SWPPP) MUST BE IN PLACE AT THE CONSTRUCTION SITE AND A WASTE DISCHARGE IDENTIFICATION NUMBER (WDID #) OBTAINED FROM THE STATE WATER BOARD. THE OWNER IS RESPONSIBLE FOR THE PREPARATION OF AND ALL REVISIONS TO THE SWPPP, INCLUDING ANY CHANGE OF INFORMATION REQUIRED BY THE GENERAL PERMIT. THE GENERAL CONTRACTOR IS RESPONSIBLE TO PAY FOR ALL ANNUAL FEES. CONTRACTOR IS ALSO RESPONSIBLE FOR THE IMPLEMENTATION OF THE SWPPP BY UTILIZING A QUALIFIED SWPPP PRACTITIONER (OSP) AS DEFINED IN THE CONSTRUCTION GENERAL PERMIT. THIS INCLUDES MAINTENANCE OF EROSION AND SEDIMENT CONTROL DURING THE LIFE OF THE PROJECT AND SUBMITTAL OF THE ANNUAL REPORTS. THE GENERAL CONTRACTOR SHALL COORDINATE WITH THE OWNER TO PROVIDE ALL APPLICABLE INFORMATION REQUESTED BY THE OWNER TO COMPLETE THE SWPPP.

CHARTRADE RAMMON ARCHITECTS Architecture • Planning • Interior Design Architecture • Planning • Interior Design COSTA MESA, CA 92627



IDENTIFICATION STAMP DIV. OF THE STATE ARCHITECT OFFICE OF REGULATION SERVICES FILE NO.: APPL. NO.: AC: FLS: SS: DATE:


COMPTON COMMUNITY COLLEGE DISTRICT COMPTON FOOTBALL FIELD 1111 E. ARTESIA BLVD., COMPTON, CA 90221 WATER POLLUTION CONTROL DETAILS

Table with 2 columns: REVISIONS, and a list of revision symbols (triangles) and numbers.

Date: 06/10/15 Job: 1529 Scale: NONE Drawn: AU

C005 SHEET - OF XREF:

PLAN PREPARED BY: FPL FPL and Associates, Inc. Traffic • Transportation • Civil Irvine, CA 92606 PHONE: 949-252-1888




- CONSTRUCTION NOTES:**
- (A) CONNECT NEW 4" WATERLINE TO EXISTING 6" WATERLINE WITH APPROPRIATE FITTINGS AND A REDUCER.
 - (B) CONSTRUCT 4" REDUCED PRESSURE PRINCIPLE ASSEMBLY PER DETAIL 'B' ON SHEET C007.
 - (C) CONSTRUCT BOOSTER PUMP ASSEMBLY PER DETAIL 'D' ON SHEET C007.
 - (D) CONSTRUCT CONTROLLER ASSEMBLY PER DETAIL 'D' ON SHEET C007.
 - (E) CONSTRUCT FIELD COOLING SYSTEM, HUNTER MODEL STK-6V, PER DETAIL 'E' ON SHEET C008.
 - (F) CONSTRUCT 3" CLASS 315 (SDR 13.5) PVC PRESSURE PIPE. SEE FIELD COOLING TRENCH DETAIL ON SHEET C003.
 - (G) CONSTRUCT 4" C-900 CLASS 235 (DR 18) PVC PRESSURE PIPE. SEE WATER PIPE TRENCH DETAIL FOR LINES 4-INCHES AND OVER ON SHEET C003.
 - (H) CONSTRUCT CONCRETE THRUST BLOCK PER DETAIL 'H' ON SHEET C007.
 - (I) CONSTRUCT 1" SCH. 80 PVC WATER PIPE. SEE FIELD COOLING TRENCH DETAIL ON SHEET C003.
 - (J) CONSTRUCT 3" MASTER CONTROL VALVE PER DETAIL 'J' ON SHEET C008.
 - (K) CONSTRUCT 3" FLOW SENSOR PER DETAIL 'K' ON SHEET C008.
 - (L) CONSTRUCT MAINLINE AIR RELEASE VALVE PER DETAIL 'L' ON SHEET C008.
 - (M) CONSTRUCT ISOLATION GATE VALVE PER DETAIL 'M' ON SHEET C008.
 - (N) HIGH VOLTAGE POWER (E1) FOR BOOSTER PUMP SYSTEM PER ELECTRICAL PLAN.
 - (O) LOW VOLTAGE POWER (E2) PER ELECTRICAL PLAN.


- LEGEND:**
- = NEW SYNTHETIC TURF
 - A** = MAINLINE AIR RELEASE VALVE
 - C** = JOHN DEERE GREEN TECH CONTROLLER
 - E1** = HIGH VOLT-3 PHASE POWER PER ELECTRICAL PLANS.
 - E2** = LOW VOLT POWER PER ELECTRICAL PLANS.
 - F1** = FLOW SENSOR
 - P** = BOOSTER PUMP
 - VI** = MASTER CONTROLLER VALVE
 - = ISOLATION GATE VALVE
 - = FIELD COOLING VAULT

CONTRACTOR SHALL PROTECT IN PLACE EXISTING TRACK SURFACING AND SUBSTRATE AT ALL TIMES.

CONTINUATION FOR QUICK COUPLER SUPPLY PIPING & FITTING
33.65' 10.81'



NOTE: CONTRACTOR IS REQUIRED TO RESTORE ALL EXISTING IMPROVEMENTS TO THE SAME CONDITION, THAT ARE NOT PART OF THIS PROJECT, THAT EXISTED PRIOR TO HIS STARTING CONSTRUCTION.





NOTE: WIRE CONNECTOR SHALL BE A 3M DBRY-6 DIRECT BURY SPLICE KIT (U.L. APPROVED). KIT SHALL INCLUDE A SCOTCHLOK Y SPRING CONNECTOR, A POLYPROPYLENE TUBE AND A WATERPROOF SEALING GEL. TUBE SHALL BE SUPPLIED PRE-FILLED WITH GEL.

WATERPROOF WIRE CONNECTION DETAIL
NOT TO SCALE

PLAN PREPARED BY:
FPL and Associates, Inc.
Traffic - Transportation - Civil
10 Corporate Park, Suite 310
Irvine, CA 92606
PHONE: 949-252-1688

GHA GHATRODE BARNUM ARCHITECTS
Architecture • Planning • Interior Design
100 W. 10th STREET, UNIT 8
COSTA MESA, CA 92626
PH: 714.888.0000
FAX: 714.888.0002
Copyright © 2015 Chataoide Barnum Architects, LLP
Architect Seal



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES


FILE NO.:
APPL. NO.:
AC: FLS: SS:
DATE:

COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221
FIELD COOLING SYSTEM PLAN

REVISIONS:

Date: 06/10/15
Job: 1529
Scale: 1" = 20'
Drawn: AU

C006
SHEET - OF
XREF:



NOTE TO CONTRACTOR (MANDATORY):
THE ENTIRE ASSEMBLY SHALL BE SET LEVEL IN A HORIZONTAL POSITION. THE DISTANCE BETWEEN THE CONCRETE SLAB AND THE LOWEST PART OF THE BACKFLOW ASSEMBLY SHALL BE 12 INCHES MINIMUM WITH A MAXIMUM OF 18 INCHES.

REDUCED PRESSURE PRINCIPLE ASSEMBLY CONSTRUCTION NOTES:

- 4" THICK CONCRETE SLAB, CONCRETE CLASS 520-C-2500.
- 4" NON-RISING STEM GATE VALVE.
- ADJUSTABLE PIPE SUPPORT, GRINNELL MODEL 4000 OR APPROVED, INSTALL BASE PLATE ON LEVELING COURSE OF HIGH STRENGTH EPOXY CEMENT COMPOUND. PIPE SUPPORTS SHALL BE PAINTED AND COATED TO MATCH BACKFLOW PREVENTER. ALL THREADED AREAS SHALL BE COATED WITH "NEVER-SEIZE" OR OTHER EQUIVALENT ANTI-RUST LUBRICANT. (PARTS TO BE STAINLESS STEEL OR HOT DIPPED GALVANIZED AFTER FABRICATION)
- 4" CLASS 235, 90° DUCTILE IRON BEND, CEMENT LINED.
- 4" X FIELD LENGTH DUCTILE IRON SPOOL, FLG. X FLG.
- CONSTRUCT CONCRETE THRUST BLOCK PER DETAILS HEREON.
- CONTRACTOR TO SUPPLY HOT DIPPED GALVANIZED CHAIN AND LOCK, LOCK HANDWHEEL ON N.R.S. VALVES IN THE OPEN POSITION, PADLOCK SHALL BE BREAKAWAY TYPE.
- 4" A.W.W.A. C-900 CL-235 P.V.C. PRESSURE PIPE.

NOTES TO CONTRACTOR:

- CONTRACTOR TO VERIFY CONDITION OF CONNECTION POINTS PRIOR TO CONSTRUCTION AND REPORT ALL DISCREPANCIES TO DESIGN ENGINEER.
- ALL BOLTS SHALL BE STAINLESS STEEL TYPE 316 PER ASTM F593 GRADE G OR H AND NUTS AND WASHERS SHALL BE STAINLESS STEEL TYPE 316 PER ASTM F594 GRADE G OR H.
- ALL GASKETS SHALL BE NITRILE OR STYRENE BUTADIENE GASKETS.
- ALL NEWLY INSTALLED BACKFLOW PREVENTION ASSEMBLIES MUST BE TESTED IN ACCORDANCE WITH APPLICABLE REGULATIONS PRIOR TO BEING PUT IN SERVICE. COPIES OF TEST RESULTS SHALL BE SUBMITTED TO LONG BEACH WATER DISTRICT PRIOR TO ACTIVATION.
- PAINT ABOVE GROUND PIPING AND VALVES WITH ONE COAT OF BLUE OXIDE PRIMER AND TWO COATS OF HIGH VISIBILITY EPOXY BLUE ENAMEL.
- DEVICES SHALL BE INSTALLED IN STRICT ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS.
- MAINTAIN 3' WIDE CLEARANCE AREA AROUND ENTIRE DEVICE FOR MAINTENANCE.



3 Chrysler, Unit 100
Irvine, CA 92618
(949) 455-7465 PH
(949) 455-7492 FX

GREEN TECH PUMP ASSEMBLY - Variable Frequency Drive Booster Pumping System


Date:	June 9, 2015	Station Model:	PA25-15022-39N-463
Quotation #:	RMG15022	Station Performance:	220 GPM @ 80 PSI Boost
Project Name:	Compton Community College District	Dynamic Inlet PSI:	45 PSI
Location:	Compton, CA	Power Requirement:	460 volt, 3 phase, 60 hertz.
Quoted By:	Ryan Griffin	Horsepower:	15 HP (3600rpm)
Sales Email:	rgriffin@johndeeregreentech.com	FLA/Disconnect:	32A

Project Scope: Prefabricated, self-contained enclosed Variable speed (VFD) 15 HP horizontal centrifugal pump station with piping and valves painted (green). Controls will be an operator interface with software programming written specifically for this project. A formed and reinforced base platform and enclosure with lockable lid contains all manifold, pumps, motors and control panels (disconnect mounted externally) to provide an integral unit ready for easy installation, anchored to a concrete pad.



STANDARD CONTROLS & EQUIPMENT INCLUDE:

- External mounted NEMA 4 service rated main disconnect panel
- U.L listed control panel
- Multi-line operator interface display featuring:
 - Flow readout
 - Pressure readout
 - Flow totalizer
 - Elapsed run time display
- Alarm conditions with safety shutdown:
 - Low discharge pressure shutdown
 - High discharge pressure shutdown
 - VFD fault shutdown
 - High pump temperature shutdown
- Overload, single phase, phase imbalance/low voltage protection
- Surge protection for main station and solid state controls
- Variable Frequency Drive pressure regulation
- 24 VAC relay start (1 controller) or Pressure Start
- Hand/off/auto selector switch
- Stainless steel pressure transducer
- Data Industrial 220B flow sensor mounted inside enclosure
- 15 HP, 3600 RPM horizontal centrifugal pump and ODP motor. Pump to be cast iron with a bronze impeller and mechanical seal.
- Silicone filled pressure gauges with isolation valve on suction and discharge piping
- Station discharge isolation valve
- 4" FL x 4" FL fabricated steel inlet drop pipe with swivel connection (Qty. 2, Inlet and discharge)
- Forced fan air cooled ventilated marine grade aluminum pump station enclosure and stainless steel base, un-painted, with lockable access cover
- Lockable dead front external disconnect panel
- Baked and cured two part polyurethane ultraviolet insensitive paint
- Factory certified dynamic run testing of pump station up to full flow and pressure prior to shipment
- One operator and maintenance manual
- One year limited warranty on mechanical and electrical components
- Access to John Deere Green Tech customer service technical phone support, technicians on call 24/7
- Access to John Deere Green Tech factory authorized service technician

5 GREEN TECH BOOSTER PUMP ASSEMBLY DETAIL
NOT TO SCALE



5 GREEN TECH PUMP ASSEMBLY (PA)
NOT TO SCALE



NOTE: THRUST BLOCKS SHALL NOT BE USED ON GATE VALVES WHICH ARE FLANGED TO TEES OR CROSSES WHICH HAVE THRUST BLOCKS.

GENERAL NOTES:

- ALL DUCTILE IRON FITTINGS BURIED UNDERGROUND SHALL BE PROTECTED WITH PLASTIC FILM WRAP IN ACCORDANCE WITH AWWA C105. WRAP SHALL BE A LOOSE 8"-MIN-THICK POLYETHYLENE TUBE. ALL JOINTS BETWEEN PLASTIC TUBES SHALL BE WRAPPED WITH 2"-INCH-WIDE POLYETHYLENE ADHESIVE TAPE, POLYKEN 900, SCOTCH WRAP 50, OR APPROVED EQUAL.
- THRUST BLOCK AREAS ARE BASED ON 200 PSI PRESSURE AND 1,000 PSF ALLOWABLE SOIL BEARING PRESSURE & SIZED PER N.F.P.A. 13, ANNEX A, TABLE A.10.8.2(a), 2002 EDITION.
- ALL BOLTS AND STUDS SHALL BE TYPE 316 STAINLESS STEEL PER ASTM A193 GRADE B8M. NUTS AND WASHERS SHALL BE TYPE 316 STAINLESS STEEL PER ASTM A194 GRADE B8M.
- THRUST BLOCKS SHALL BE INSTALLED AT EVERY CHANGE OF DIRECTION.
- ALL THRUST BLOCKS SHOULD, WHERE POSSIBLE, BE PLACED AGAINST UNDISTURBED SOIL. WHERE IT IS NOT POSSIBLE TO PLACE THE BEARING SURFACE AGAINST UNDISTURBED SOIL, THE FILL BETWEEN THE BEARING SURFACE AND UNDISTURBED SOIL MUST BE COMPACTED TO AT LEAST 90% STANDARD PROCTOR DENSITY (PER N.F.P.A. 13, ANNEX A.10.8.2, 2002 EDITION). THEY SHALL BE CENTERED VERTICALLY AND HORIZONTALLY ABOUT THE DIRECTION OF THE THRUST.
- THRUST BLOCKS SHALL BE CONCRETE CLASS 520-C-2500 PER THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 2009 EDITION, SECTION 201-1 WITH TYPE II CEMENT.
- WHERE WATER MAIN DEAD ENDS ARE BLIND FLANGED OR CAPPED, THE THRUST BLOCK SHALL EXTEND A MINIMUM DISTANCE OF 6" INTO BOTH SIDES OF THE TRENCH.
- CONCRETE POURED AGAINST PIPE FITTINGS SHALL BE PLACED SO THAT VALVES AND FITTINGS ARE ACCESSIBLE FOR REPAIR.
- TIE BARS SHALL BE #4 REBAR (PER ASTM 767 AND D3963) OR STAINLESS STEEL WITH AGI HOOKED ENDS. WHEN TIE BARS ARE NOT EMBEDDED IN CONCRETE THEY SHALL BE COATED WITH KOPPERS CO. BITUMASTIC NO. 50 OR EQUIVALENT.
- ALL EXPOSED FLANGES AND OTHER METAL SURFACES AND ALL DAMAGED COATINGS SHALL BE COATED AFTER ASSEMBLY WITH A MASTIC, PER SPECIFICATIONS.
- CONCRETE SHALL HAVE 3" MINIMUM CLEARANCE AROUND ALL JOINTS.

H ON-SITE THRUST BLOCK DETAILS
NOT TO SCALE



Compton Community College District

CA6-TC3-12+1 / FSMVC -300S

Controller Assembly = CA
Enclosure Type = 6
Touch Screen Model = TC3
Station Count = 24+1 Master Valve
Flow Sensing = Monitor with 3" Insert and Saddle
Master Valve = Normally Closed 3"

Touch Control Specifications

DESCRIPTION

The John Deere-Green Tech Touch Control (TC) is a versatile product that has a modular design and can be used in a variety of specialty applications. The TC product line is highly customizable and can be uniquely configured for individual clients.

The TC comes in three basic styles: 1) PLC only, 2) PLC with monochrome Touch Screen, 3) PLC with color Touch Screen.

TC has seven application types 1) Fertilization/chemigation, 2) Filtration, 3) Lighting, 4) Moisture Sensing, 5) Pump, 6) Sports Field, 7) Water Harvesting.

The TC product line utilizes the VIT enclosures listed below:

- 18"W x 36"H x 12"D Front Entry
- 18"W x 36"H x 24"D Front & Rear Door
- 24"W x 36"H x 12"D Front Entry
- 24"W x 36"H x 24"D Front & Rear Door
- 18"W x 52"H x 32"D Metered
- 16"W x 38"H x 15.5"D Top Entry
- 24"W x 38"H x 17"D Top Entry
- 36"W x 36"H x 12"D Double Wide
- 16"W x 32"H Backboard only Wall Mount
- 22"W x 32"H Backboard only Wall Mount
- 16.75"W x 30"H x 8.25"D Light Duty Wall Mount
- 18"W x 36"H x 12"D Front Entry Wall Mount



3 Chrysler • Irvine, CA 92618 • Tel: 949-455-7465 • 909-427-0779 • Fax: 949-455-7492 • Fax: 866-447-9873

D CONTROLLER ASSEMBLY DETAIL
NOT TO SCALE

TC3

Operating Voltage	24V DC
Input Voltage	120VAC
Touch Screen	5.7" TFT Color
Color Depth	65,536
Effective Display Area	4.6" x 3.4"
Brightness	800 cd/m2
Resolution	640 x 480 pixels.
Memory capacity	12MB
Serial ports/communication	2/Modbus (RS232, RS485, RS422)
Ethernet ports/communication	1/RJ-45
USB ports/communication	1/TypeA & 1/MiniB
Remote Monitor	Yes
Approvals	UL 1604, Hazardous Locations
NEMA Type	13

FSMVC-300S

FLOW SENSOR MONITOR
Rain Bird pulse decoder and Data Industrial Model# FT1502 flow monitor for use with Maxicom. Monitors and displays flow.

FLOW SENSOR

3" Data Industrial flow sensor. The sensor shall operate in-line pressures up to 125 psi and liquid temperatures up to 140° F, and operate in flows of 1 foot per second to 30 feet per second. Includes Saddle for 4" mainline.

MASTER VALVE


3000 Series 3" Superior MV - Normally Closed
For flows 5-320gpm. Operating pressure up to 200psi.

3000 Series

Normally Closed





Size	Model	Operating Pressure	Flow
1.5"	300012P	5-10	1
1.5"	300012E	5-10	1
2"	300022P	10-20	1
2"	300022E	10-20	1



D SWITCH CONTROLLER SECTION
NOT TO SCALE

GHATRODE BRANNON ARCHITECTS
Architecture • Planning • Interior Design
100 W. 10th Street, Unit 8
Costa Mesa, CA 92626
PH: 714.468.0000
FAX: 714.468.0000



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES

FILE NO.:
APPL. NO.:
AC: FLS SS
DATE:

COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221
FIELD COOLING SYSTEM DETAILS

REVISIONS:


1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			

Date: 06/10/15
Job: 1529
Scale: NONE
Drawn: AU

C007
SHEET - OF
XREF:


PLAN PREPARED BY:
FPL FPL and Associates, Inc.
Traffic - Transportation - Civil
10 Corporate Park, Suite 310
Irvine, CA 92606
PHONE: 949-252-1688

STK-6V
SYNTHETIC TURF VAH ROTOR & ENCLOSURE SYSTEM
TOP VIEW
"OFF FIELD SIDE"




- 1 HUNTER ST-243636B COMPOSITE VAULT & 4-PIECE POLYMER-CONCRETE COVER SET WITH CAST-IN OPENINGS TO SUPPORT ROTOR LATERAL THRUST PLUS CAST IN OPENING WITH CIRCULAR COVERS FOR QUICK COUPLER AND ON-OFF-AUTO SELECTOR ACCESS
- 2 INFILL SYNTHETIC TURF MATERIAL ATTACHED TO VAULT RIM AND COVER SET
- 3 FINISHED GRADE SET TO FIELD PERIMETER TACK/GLUE BOARD OR AS PER SPECIFICATION
- 4 2" X 4" (50mm X 102mm) TACK/GLUE BOARD AS PER SPECIFICATION ALL SIDES
- 5 HUNTER ST-V30KV ULTRA LOW LOSS 3" (80mm) VALVE KIT WITH GROOVED FITTING CONNECTIONS
- 6 REMOTE ON-OFF-AUTO SELECTOR AND SOLENOID MANIFOLD ASSEMBLY MOUNTED ON VAULT SIDEWALL
- 7 COLOR CODED CONTROL TUBING FROM ST-V30KV VALVE TO SELECTOR SWITCH MOUNTED ON VAULT SIDE WALL
- 8 LEAD WIRES FROM SOLENOID TO WATERPROOF SPLICE CONNECTORS
- 9 HUNTER ST-BVF30K ISOLATION VALVE AND FITTING KIT WITH GROOVED CONNECTIONS AND 500 PSI RATED COUPLINGS SUFFICIENT TO CONNECT ROTOR AND CONTROL VALVE TO MANIFOLD INLET
- 10 HUNTER ST-SPTK ADJUSTABLE MANIFOLD SUPPORT BLOCK ADJUSTED TO SUPPORT MANIFOLD WEIGHT TWO (2) REQUIRED
- 11 SUPPORT PAD AS 16" X 16" X 2" (41cm X 41cm X 50mm) CONCRETE STEPPING STONE OR AS PER SPECIFICATION (2)
- 12 HUNTER HQ-SRC QUICK COUPLING VALVE SET DIRECTLY BELOW CIRCULAR QUICK-ACCESS PORT
- 13 HUNTER ST-H30K 3" (80mm) STAINLESS STEEL FLEXIBLE INLET PIPE
- 14 1" (25mm) MINIMUM SCH 80 QUICK COUPLER SUPPLY PIPING AND FITTINGS OR AS PER SPECIFICATION
- 15 3/4" X 48" (16mm X 122cm) REBAR STAKE WITH STAINLESS STEEL STRAPPING
- 16 COMPACTED BASE FIELD MATERIALS PER SPECIFICATIONS
- 17 BRASS MANUAL BALL VALVE INCLUDED/PROVIDED WITH #8 ST-BVF30K
- 18 PROVIDE DRAINAGE VIA ACCESS TO FIELD DRAINAGE SYSTEM
- 19 WATERPROOF CONNECTIONS PER SPECIFICATIONS BETWEEN CONTROL WIRE AND SOLENOID LEAD WIRES
- 20 TOP OF QUICK COUPLER SET LESS THAN 1/2" BELOW UNDERSIDE OF MAIN VAULT COVER TO ALLOW KEY ACTIVATION FROM ABOVE
- 21 HUNTER ST-BS1600 RUBBER COVER AND INFILL BARRIER KIT WITH TRIM REFERENCE RINGS TO ALLOW HEIGHTS FROM STANDARD 1-1/4" (32mm) (INFILL APPLICATION) TO FLAT (NON-INFILL OR TRACK MATERIAL) APPLICATIONS
- 22 HUNTER ST-BKT1600 ROTOR HANGER AND ELEVATION ADJUSTMENT BRACKET
- 23 HUNTER ST-1600B ROTOR
- 24 ISOLATION BUTTERFLY VALVE WITH GROOVED CONNECTIONS INCLUDED/PROVIDED WITH #8 ST-BVF30K
- 25 INFILL SYNTHETIC TURF MATERIAL ATTACHED TO ST-BS1600 CUP USING HUNTER ST-ADH ADHESIVE AND APPROVED PROCEDURES.
- 26 WRAP FLEXIBLE INLET PIPING WITH HEAVY-DUTY PLASTIC PIPE WRAP TAPE PRIOR TO BACK-FILL AND COMPACTION

"ON FIELD SIDE"



STK-6V SIDE VIEW "INFILL TURF OVER VAULT"
"VIEW FROM ON FIELD SIDE"




STK-6V ZOOM VIEW "INFILL TURF OVER VAULT"
"VIEW FROM ON FIELD SIDE"

E FIELD COOLING SYSTEM DETAIL
NOT TO SCALE


- 1 HUNTER ST-243636B COMPOSITE VAULT & 4-PIECE POLYMER-CONCRETE COVER SET WITH CAST-IN OPENINGS TO SUPPORT ROTOR LATERAL THRUST PLUS CAST IN OPENING WITH CIRCULAR COVERS FOR QUICK COUPLER AND ON-OFF-AUTO SELECTOR ACCESS
- 2 2" X 4" (50mm X 102mm) TACK/GLUE BOARD AS PER SPECIFICATION ALL SIDES
- 3 INFILL SYNTHETIC TURF MATERIAL ATTACHED TO VAULT RIM AND COVER SET
- 4 FINISHED GRADE
- 5 BASE PAD AS PER SPECIFICATION
- 6 STRUCTURAL BASE ROCK (SEE TURF BASE CONSTRUCTION)
- 7 GEOTEXTILE CLOTH LAYER OR AS PER SPECIFICATION
- 8 NATURAL SOIL (SEE TURF BASE CONSTRUCTION)
- 9 HUNTER VAULT SIDEWALL AND RIM
- 10 INFILL SYNTHETIC TURF MATERIAL ATTACHED TO FLATTENED ST-BS1600 USING HUNTER ST-ADH ADHESIVE AND APPROVED PROCEDURES
- 11 HUNTER ST-BS1600 INFILL BARRIER RUBBER COVER TRIMMED FLAT
- 12 HUNTER ST-BKT1600 ROTOR HANGER AND ELEVATION ADJUSTMENT BRACKET

- ENCLOSURE DIMENSIONS**
- 4 - PIECE COVER - 24" X 36" (50cm X 76cm)
 - EXPOSED RIM - 26" X 38" (66cm X 96.5cm)
 - OVERALL HEIGHT - 36" (76cm)
 - BASE PAD - 42" X 48" (107cm X 122cm)




NOTE:
USE STANDARD OPENINGS PROVIDED IN VALVE BOX FOR PIPE. DO NOT CUT BOX.
FOR MCVS ON COOLING SYSTEM USING POTABLE WATER, DELETE ALL RECYCLED WARNING TAGS.

J MASTER CONTROL VALVE (V1)
NOT TO SCALE




NOTE:
USE STANDARD OPENINGS PROVIDED IN VALVE BOX FOR PIPE. DO NOT CUT BOX.
FOR FS'S ON COOLING SYSTEM USING POTABLE WATER, DELETE ALL RECYCLED WARNING TAGS.

K FLOW SENSOR (F1)
NOT TO SCALE




NOTE:
A MINIMUM OF ONE GROUND ROD SHALL BE INSTALLED PER CONTROLLER. SEE LEGEND, DETAILS AND SPECIFICATIONS FOR ADDITIONAL GROUNDING REQUIREMENTS.

CONTROLLER GROUNDING DETAIL
NOT TO SCALE
NOTE: A MINIMUM OF ONE GROUND ROD SHALL BE INSTALLED PER CONTROLLER.






NOTE:
INSTALL AIR RELIEF VALVE AT HIGH POINT ON MAINLINE.
MAINLINE PIPE SLOPE SHOWN EXAGGERATED ON DETAIL FOR CLARITY.

L MAINLINE AIR RELEASE VALVE
NOT TO SCALE



NOTE:
USE STANDARD OPENINGS PROVIDED IN VALVE BOX FOR PIPE. DO NOT CUT BOX.
FOR GVS ON COOLING SYSTEM USING POTABLE WATER, DELETE ALL RECYCLED WARNING TAGS.

M MAINLINE ISOLATION GATE VALVE
NOT TO SCALE



REVISIONS:

Date: 06/10/15
Job: 1529
Scale: NONE
Drawn: AU

KEYNOTES GENERALLY CORRESPOND TO SPECIFICATION SECTIONS BY MEANS OF THE SIX-DIGIT NUMBER IDENTIFYING THE SPECIFICATION SECTION AS A MATTER OF REFERENCE AND CONVENIENCE. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL WORK INDICATED HEREIN PERTINENT TO THE GENERAL CONDITIONS AND TECHNICAL SPECIFICATIONS OF THE CONTRACT, REGARDLESS OF WHETHER OR NOT THE KEYNOTE(S) SPECIFICALLY CORRESPOND TO ANY SPECIFICATION DIVISION PROVIDED IN THE TECHNICAL SPECIFICATIONS.

KEYNOTES

- DIVISION 02 - EXISTING CONDITIONS**
 02 41 00.E1 - EXISTING ITEM TO REMAIN
- DIVISION 11 - EQUIPMENT**
 11 68 33.C1 - ELECTRICAL COMMUNICATION BOX
 11 68 33.G1 - FOOTBALL GOAL POST OFOI
- DIVISION 32 - EXTERIOR IMPROVEMENTS**
 32 12 16.A1 - HOT-MIX ASPHALT PAVING
 32 18 13.A1 - SYNTHETIC GRASS SURFACING OFOI
- DIVISION 33 - UTILITIES**
 33 40 00.S1 - SLOT DRAIN



SITE NOTES

- FOR TYPICAL SYMBOLS AND ABBREVIATIONS, SEE SHEET 0001.
- PROTECT AND SAFEGUARD FROM DAMAGES ALL EXISTING CONSTRUCTION AND FINISHES TO REMAIN.
- PROVIDE TEMPORARY 6' HIGH CHAIN LINK FENCE ENCLOSURES WITH LOCKABLE GATES AS REQUIRED FOR CONSTRUCTION ACCESS AT CONTRACTOR'S STAGING AREA AND AROUND ALL CONSTRUCTION SITES.
- WHERE REMOVAL OF CONCRETE WALKS, MOWSTRIPS, CURBS AND GUTTERS IS REQUIRED BY THE EXECUTION OF THIS CONTRACT, REMOVE THE CONCRETE WORK TO THE NEAREST EXISTING EXPANSION OR CONTROL JOINT (SAWCUT IF REQUIRED). CURBS AND GUTTERS MAY BE REMOVED IN MINIMUM LENGTHS OF 6' IF THE DISTANCE BETWEEN EXISTING JOINTS IS 12' OR MORE. REPLACE REMOVED WORK WITH REINFORCED CONCRETE TO MATCH ADJACENT EXISTING WORK IN PROFILE, JOINT LAYOUT AND FINISH. SEE SHEET A004 FOR SIMILAR DETAILS AND REINFORCING REQUIREMENTS. DOWEL NEW CONCRETE WORK INTO EXISTING PER DETAIL 1/A007.
- WHERE ASPHALT PAVING IS DAMAGED BY THE EXECUTION OF THIS CONTRACT, PATCH & REPAIR TO ORIGINAL OR BETTER CONDITION. WHERE (E) LAWNS ARE DAMAGED BY THE EXECUTION OF THIS CONTRACT, FILL, COMPACT, AND REPLANT AREA TO MATCH EXISTING TURF AREA.
- CONTRACTOR SHALL MAINTAIN EXISTING PLANTING WITHIN THE JOB SITE FENCE ENCLOSURE DURING DEMOLITION AND CONSTRUCTION PHASES. EXISTING IRRIGATION SYSTEMS SHALL EITHER REMAIN OPERATIONAL FOR CONTRACTOR'S USE OR CONTRACTOR SHALL HAND WATER EXISTING PLANT MATERIALS AT LEAST ONCE A WEEK.
- REPAIR EXISTING IRRIGATION SYSTEMS DAMAGED DURING THE EXECUTION OF THIS CONTRACT. REPLACE PLANT MATERIALS DAMAGED DURING THE CONSTRUCTION PERIOD WITH THE SAME SPECIES OF EQUAL OR GREATER SIZE.
- OPENINGS IN GRATING OR STRAINERS LOCATED IN PEDESTRIAN WAYS OR IN THE POT SHALL NOT ALLOW THE PASSAGE OF A SPHERE MORE THAN 3" DIAMETER. ELONGATED OPENINGS SHALL BE PLACED SO THAT THE LONG DIMENSION IS PERPENDICULAR TO THE DOMINANT DIRECTION OF TRAVEL IN COMPLIANCE WITH SECTION 11B-302.3.


SITE PLAN LEGEND

- (N) 2" SYNTHETIC TURF OVER 3/4" DRAINAGE LAYER, OVER A.C. PAVING, BASE AND OVER COMPACTED SUBGRADE. REFER TO CIVIL FOR ADDITIONAL REQUIREMENTS
- X-X-X- EXISTING CHAINLINK FENCE TO REMAIN.

KEY MAP



GHATRODE BARNON ARCHITECTS
 Architecture • Planning • Interior Design
 1111 E. ARTESIA BLVD., SUITE 100
 COSTA MESA, CA 92627
 TEL: 714.443.8029
 Copyright © 2015 Ghatrode Barnon Architects, LLP



Consultant Seal

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 OFFICE OF REGULATION SERVICES

FILE NO.:
 APPL. NO.:

AC: _____ FL: _____ SS: _____
 DATE: _____


COMPTON COMMUNITY COLLEGE DISTRICT
 COMPTON FOOTBALL FIELD
 1111 E. ARTESIA BLVD., COMPTON, CA 90221

REVISIONS:


Date: 06/08/15
 Job: 1529
 Scale:
 Drawn:

A001
 SHEET - OF XXX
 XREF:


SITE PLAN 1
 1"=30'-0"




YARDLINE LETTERING 26
3/8"=1'-0"




SIDELINE 27
1/2"=1'-0"




KICKOFF MARKER 28
3/4"=1'-0"




INBOARD LINES 29
3/4"=1'-0"




50 YARDLINE 30
3/4"=1'-0"




FOOTBALL FIELD LAYOUT 2
1/16"=1'-0"




SURFACE TRANSITION @ TURF 19



FOOTBALL GOAL FOUNDATION 14
1/12"=1'-0"




FOOTBALL GOAL 9
1/2"=1'-0"




FOOTBALL GOAL 5
1/8"=1'-0"



SLOT DRAIN 20




FOOTBALL GOAL 10
1/12"=1'-0"



FOOTBALL GOAL 5
1/8"=1'-0"

KEYNOTES GENERALLY CORRESPOND TO SPECIFICATION SECTIONS BY MEANS OF THE SIX-DIGIT NUMBER IDENTIFYING THE SPECIFICATION SECTION AS A MATTER OF REFERENCE AND CONVENIENCE. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL WORK INDICATED HEREIN PERTINENT TO THE GENERAL CONDITIONS AND TECHNICAL SPECIFICATIONS OF THE CONTRACT, REGARDLESS OF WHETHER OR NOT THE KEYNOTE(S) SPECIFICALLY CORRESPOND TO ANY SPECIFICATION DIVISION PROVIDED IN THE TECHNICAL SPECIFICATIONS.




KEY MAP 5

FOOTBALL FIELD NOTES


- TURF VENDOR SHALL VERIFY ALL DIMS W/ NFSHS STANDARDS.
- ALL LINE WORK IS TO BE LAID OUT W/IN A TOLERANCE OF 1/4".
- ALL YARDLINE SHALL BE 4", WHITE, TUFTED TURF. REFER TO FOOTBALL FIELD LAYOUT.
- A 6'-0" WHITE, TUFTED TURF BORDER SHALL SURROUND THE ENTIRE PLAYING FIELD. REFER TO FOOTBALL FIELD LAYOUT.
- 24" YARDLINE EXTENSION, 4" FROM THE SIDELINES SHALL BE 4" WIDE, WHITE, INLAID LINES. REFER TO FOOTBALL FIELD LAYOUT.
- THE COACHING BOX AND TEAM AREA SHALL BE PER NFSHSA RULES AND SHALL BE OUTLINED IN 4" WHITE INLAID TURF. REFER TO FOOTBALL FOOTBALL FIELD LAYOUT.
- THE INBOUND LINES ARE 53'-4" FROM EACH SIDELINE. INBOUND LINES AND YARDLINE EXTENSIONS SHALL BE 24" LONG AND 4" WIDE, INLAID WHITE LINES. REFER TO FOOTBALL FIELD LAYOUT.
- THE EXTRA POINT LINES ARE 6' LONG, 4" WIDE, WHITE INLAID LINES AT THE CENTERLINE OF THE FIELD AND ON THE 3 YARDLINE AT EA END OF THE FIELD. REFER TO FOOTBALL FIELD LAYOUT FOR LOCATION.
- WHITE YARDLINE NUMBERS MEASURE 6" IN HEIGHT AND 4" IN WIDTH. TOP OF NUMBERS ARE LOCATED 27" FROM THE INBOUND LINES AND ARE INLAID IN WHITE TURF. REFER TO DETAIL.
- DIRECTIONAL ARROWS POINT TOWARD RESPECTIVE END ZONES AND ARE WHITE, INLAID TURF AS DIMENSIONED ON DETAIL THERE ARE NO ARROW ON THE 50 YARDLINE.
- AN X WILL MARK THE KICKOFF LOCATION ON THE 40 YARDLINE AT EA END OF THE FIELD AND SHALL BE DIM AS PER DETAIL THE 40 YARDLINE IS WHITE TUFTED TURF AND THE LINES WHICH FORM THE X ARE INLAID WHITE.
- (12) PYLONS SHALL BE LOCATED AT THE INTERSECTIONS OF GOAL LINES AND ENDLINES W/ THE SIDELINES, AND @ THE ENDLINES, AND THE EXTENSION OF THE INBOUND LINE AND SHALL BE 4". THE PYLONS TO BE SUPPLIED BY CONTRACTOR PER SPEC.
- NUMBERED SIDELINE YARD MARKERS, CHAIN SET, AND DOWN BAX SET TO BE PROVIDED BY CONTRACTOR PER SPEC.

REVISIONS:



FOOTBALL FIELD 5

GARRODE BARNON ARCHITECTS
Architecture • Planning • Interior Design
COSTA MESA, CA 92627
Tel: 714.885.8029



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES
FILE NO.:
APPL. NO.:
AC: _____ FLS: _____ SS: _____
DATE: _____

COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221

FOOTBALL FIELD LAYOUT + DETAILS

COMPTON COMMUNITY COLLEGE DISTRICT
COMPTON FOOTBALL FIELD
1111 E. ARTESIA BLVD., COMPTON, CA 90221

Date: 06/08/15
Job: 1529
Scale:
Drawn:
A002
SHEET - OF XXX
XREF: